

Panasonic luft/luft varmepumpe

E18GFEW-2 GULVMODELL



BauerEnergi

Laget for norsk klima • Lavt energiforbruk • Lavt lydnivå



COP **3,63**
(E18GFEW-2)



ENERGIKLASSE



LYDNIVÅ (innedel)



KVALITETER



TEKNISKE SPESIFIKASJONER

MODELL INNE
MODELL UTE

CS-E18GFEW-2
CU-E18GFE-2

MODELL INNE
MODELL UTE

CS-E18GFEW-2
CU-E18GFE-2

Oppvarming

| | |
|-------------------|----------|
| Varmekapasitet W | 900-7100 |
| Virkningsgrad COP | 3,63 |
| Forbruk W | 260-2350 |

Kjøling

| | |
|-------------------|----------|
| Kjølekapasitet W | 900-5600 |
| Virkningsgrad EER | 3,53 |
| Forbruk W | 255-1910 |

Lydnivå (dB)

| | |
|----------------------------|-------|
| Lyd inne min/max (varme) | 32/44 |
| Lyd inne min/max (kjøling) | 32/44 |
| Lyd ute varme/kjøling | 48/48 |

Sirkulasjon

| | |
|---|------|
| Avfukting l/time | 2,8 |
| Luftsirkulasjon varme m ³ /min | 13,6 |

Dimensjoner

| | |
|-------------------------|-------------|
| Dimensjon H/B/D inne mm | 600/700/210 |
| Dimensjon H/B/D ute mm | 750/875/345 |
| Dimensjon rør væske | 1/4" |
| Dimensjon rør gass | 1/2" |
| Rørlengde min/max m | 3/10 (20*) |

* Maks lengde ved påfylling av ekstra gass

Autorisert forhandler

Ring gratis til vår
forhandlertelefon:

02555

www.bauerenergi.no

Velkommen til et bedre innemiljø